



# 1.054 Mechanics & Design of Concrete Structures

## Seismic Isolation Using Passive Control Technologies

Bassam William DAHER

The background of the slide features several decorative, semi-transparent blue concentric circles of varying sizes, resembling ripples on water, scattered across the lower half of the slide.

# Isolated-Base vs Fixed Base



# Seismic Isolation Using Passive Control Technologies

- Introduction
- Applications around the Globe
- Standards and Codes for Design
- Experimental results

# Traditional Anti-Seismic Structure

- Allowing Struct. Elements or joints to work to dissipate the energy
  - Not very safe
  - Limited use
  - Stronger elements -> Larger stiffness -> larger seismic load
  - Stronger elements -> Higher Cost
- 

# Seismic Control

- Passive Control : no external power source
- Active Control : external power source



# Types of Isolators

- 1-Sand Layer
- 2-Graphite-lime mortar layer
- 3-Sliding friction layer
- 4-Rollers
- 5-Rubber Bearings
- 1,2,3 are too sensitive to foundation settlement
- 4 need careful maintenance
- 5 most widely used : no moving parts, unaffected by time, resistant to environment

# Isolator Role

- Reduce the response of the structure
- Installed between foundation & struct. Or relevant parts of structure
- Extend the natural period of the structure
- Acceleration response is reduced

# Isolated-Base vs Fixed Base



# Features

- Response can be reduced to 1/2 to 1/8
- Bldg costs can be reduced 3 to 15%
- Wide range of application : New and Old
- Freedom of architectural design : can be used in bldgs with irregular configurations

# Rubber Bearing

- Steel and Rubber sheets



# Rubber Bearing

- Steel, Rubber, and Lead Core



# Rubber Bearing Features

- Effective isolation,  $\frac{1}{2}$  to  $\frac{1}{8}$  tradit.response
- Stable no maintenance lifetime >100 years
- They recover from displacement perfectly
- Can accommodate vertical motion of bldg
- Insensitivity to foundation settlement
- They have operated successfully USA,China, Japan
- They decrease temperature stress in structures by horiz. deform. During large change of  $T^{\circ}$

# US Applications

- 1994 Northridge EQ
- USC Hospital 8 stories
- supported on 68 lead rubber isolators and 81 elastomeric isolators
- The PGA outside the building was 0.49 g, and the accelerations inside the building were around 0.10 to 0.13 g.

# JAPAN Applications

- largest base-isolated building in the world
- West Japan Postal Computer Center, Kobe
- This six-storey, (500,000 ft square) structure
- Supported on 120 elastomeric isolators isolated
- Isolated period of 3.9 sec
- PGA = 0.41 g
- Reduced by the isolation system to (0.13 g) at 6th floor.

# ARMENIA Applications

## Design & Cost Comparison of 4 storey building

Values compared	Fixed-base building	Seismically isolated building
Total shear fore (kN)	40800	10200
Required reinforcement (t)	360	104
Required reinforcement per 1 m <sup>2</sup> of the area of the building (kg)	110	32
Distance (cm) between the reinforcing bars and their average diameter (mm) in the walls	20 × 20, Ø16	40 × 40, Ø8
Required strength of the concrete (N/cm <sup>2</sup> )	2500	1500
Required cement (t)	810	428
Required cement per 1 m <sup>2</sup> of the area of the building (kg)	250	132
Cost of reinforcement (US\$)	144000	41600
Cost of cement (US\$)	32210	17550
Cost of seismic isolators (US\$)		24700

Savings = (144,000+32,210) – (41,600+17,550+24,700) = \$92,360

Cost of bearing structure = \$ 27,000

Total Savings = \$ 65,360 = 30% Savings

# NEW ZEALAND Application

- Museum of NZ Te Papa , Wellington
- Heaviest seismically isolated in the world
- 190 x 104 m, , 23 m height
- 5 storey , 35000 sq m
- Required to Suffer no damage in 250 years !!!
- No collapse with a 2000 years earthquake
- 142 lead rubber bearings , with Teflon slidings under shear walls

# NEW ZEALAND Application

	250 year	2000 year
Isolated Max floor accel.	0.33 g	0.48 g
Fixed base max. floor accel	1.02 g	1.69 g
Displacement-Isolated	260 mm	510 mm

Period of isolated structure = 2.5 s

# NEW ZEALAND Application


Results of Feasibility study on damage costs to content and structure  
Museum of NZ Te Papa




# Simulation

- We used a Java powered simulation program developed by Prof.B.F Spencer Jr. from the UIUC
- a SDOF (single degree of freedom) frame
- Structure : 100 tons , 1 Hz, damping ratio is 5%.
- Isolation system : mass ratio (mass of base slab divided by mass of superstructure) is 0.10 ,
- natural frequency 0.5 Hz,
- the damping ratio will be varied between 5 and 20%
- Frequency will be varied between 0.7 Hz and 0.3Hz
- El Centro Earthquake


Max Velocity vs Damper's Period in Seconds



Max Acceleration vs Damper Period



Max Displacement vs Damper's Period



frequency (Hz)	0.7	0.6	0.5	0.4	0.3	Damping
period (sec)	1.43	1.67	2.00	2.50	3.33	
Max.displacement mm	84.8	63.8	54.7	43.9	31.8	20%
	86.9	64	54.4	43.1	30.6	15%
	90.4	65.3	54.8	42.9	29.7	10%
	95.6	69.1	55.9	43.5	29.6	5%
	41.89	33.39	24.57	16.22	9.37	20%
	42.01	33.06	23.73	15	8.65	15%
Max Velocity cm/s	42.69	33.21	23.35	14.13	8.15	10%
	44.06	34.01	23.49	14.01	8.05	5%
	0.343	0.258	0.221	0.177	0.129	20%
	0.351	0.259	0.220	0.174	0.123	15%
	0.365	0.264	0.221	0.173	0.120	10%
	0.386	0.279	0.226	0.176	0.119	5%
Max Acceleration g						

# Interpretation-1

## Maximum Displacement

- Fixed Base 745.1 mm
- Isolated 95.6 mm
- Reduction 8 times

# Interpretation-2

## Maximum Velocity

- Fixed Base 467.26 cm/s
- Isolated 44.06 cm/s
- Reduction 10 times

# Interpretation-3

## Maximum Acceleration

- Fixed Base 3.0157 g
- Isolated 0.386 g
- Reduction 8 times

# Interpretation

- Reduction up to 8 times in the acceleration, velocity and displacement
- In accordance with the most optimistic results from literature review (case of China).

# Conclusions

- Innovative technique to protect buildings
- Not widespread use
- Significant Cost and Risk Reductions
- Successful Real life examples (USC, Kobe)
- Standardization will improve proliferation
- Simulation results in accordance with literature conclusions

# References

- 1-Mazzolani FM & Serino G. Most recent developments and applications of seismic isolation of civil buildings in Italy. *Proceedings of the International Post-SmiRT Conference Seminar on Isolation ,Energy Dissipation and Control of Vibrations of Structures*, Capri, Italy, 23-25 August 1993: 71-110
- 2- Mazzolani FM .Passive control technologies for seismic-resistant buildings in Europe.*Progress in Structural Engineering and Materials*.Volume 3, Issue 3, Date: July/September 2001, Pages: 277-287
- 3- Zhou FL. Seismic isolation of civil buildings in the People's Republic of China.*Progress in Structural Engineering and Materials*.Volume 3, Issue 3, Date: July/September 2001, Pages: 268-276
- 4- Dolce M. Design guidelines for isolated buildings in Italy *International Post-SmiRT Conference Seminar on Isolation ,Energy Dissipation and Control of Vibrations of Structures*, Capri, Italy, 23-25 August 1993
- 5- Melkumyan MG . Seismic isolation of civil buildings in Armenia.*Progress in Structural Engineering and Materials*.Volume 4, Issue 4, Date: October/December 2002, Pages: 344-352
- 6- Robinson WH . Seismic isolation of civil buildings in New Zealand.*Progress in Structural Engineering and Materials*.Volume 2, Issue 3, Date: July/September 2000, Pages: 328-334
- 7- Kelly JM . Base Isolation. Origins and Development. *EERC News*, Volume 12, Issue 1, January 1991.
- 8- Poole RA , Clendon JE. New Zealand Parliament buildings: seismic protection by base isolation. *Bulletin of the New Zealand National Society for Earthquake Engineering*1992: Volume 25, Issue 3, Pages: 147-160.
- 9-Boardman PR & Kelly TP. Seismic design of the Museum of New Zealand. *Technical Conference*. New Zealand National Society for Earthquake Engineering. 1993. Page 80.
- 10-Zongjian Lan et al. An Experimental Study on Seismic Responses of Multifunctional Vibration-absorption Reinforced Concrete Megaframe Structures. *Earthquake Engineering and Structural Dynamics*. Volume 33, Issue 1, Date: January 2004, Pages: 1-14.
- 11-B.F Spencer Jr. Java Powered simulation for Base Isolation. *Multidisciplinary Center for Earthquake Engineering Research (MCEER)*. University of Illinois at Urbana Champaign.