Lecture, 22 - Biological Nitrogen Removal Total N after secondary treatment \$ 25-30 mg/L Biological N removal can reduce to 5 5-8 mg/L Nitrification: two-step process: (see Mile Fig 7-21, pg 2) 1. oxidation of ammonia, NH4, to nitrite, NO2  $2 \text{ NH}_{4}^{+} + 30_{2} \xrightarrow{\text{nitroso-bacteria}} 2 \text{ NO}_{2}^{-} + 4 \text{H}^{+} + 2\text{H}_{2}\text{O}$ 2. oxidation of nitrite NO2 to nitrate NO2 2 NO2 + O2 nitro-bacteria 2NO2 Nitrification is slightly less thermodynamically favorable than oxidation with oxygen, but both can proceed in biological treatment such as AST Nitrifying bacteria grow more slowly than heterotrophic bacteria and have lower cell yield - longer detention times needed to achieve nitrification in AST Overall reaction NH4 + 20, -> 2H+ + H20 1 gram N uses 4.57 grams O2 based on stoichiometry In actuality, less 02 is needed since 0 is generated by fixing CO2 and N into cell mass. This uses [AIK]: NH4 + 2HCO3 + 20, -> NO3 + 200, + 3H20 1 gram N uses 7.14 g Alk as CaCO3



Figure by MIT OCW.

Adapted from: G. Tchobanoglous, F. L. Burton, and H. D. Stensel. *Wastewater Engineering: Treatment and Reuse*. 4th ed. Metcalf & Eddy Inc., New York, NY: McGraw-Hill, 2003, p. 617.

3, Both reactions actually contribute. Overall reaction is estimated as: NH1 + 1.863 0, + 0.098 CO2 -> 0.0196 C6H7NO2 + 0.98 NO2 + (new cells) 0.0941 H20 + 1.98 H+ For each gram of N, 4.25 g Oz used, 0.16 g new cells formed, 7.07 g Alk as CaCO2 used Deputrification Bacteria oxidize organic substrate using intrate/netrite as electron acceptor Nitrate goes as: NO3 -> NO2 -> NO -> N20 -> N2 Organic substrate may be wastewater = C10 H19 03 N + 10 NO3 -> 5 N2 + 10 CO, + 3H20 + NH2 + 10 0Hoccurs under anoxic conditions in preanoxic Nitrate feed process: Anoxic Aerobic/ -Influentnitrification Return activated ź sludge sludge Sometimes called "substrate-driven" denitrification Wastewater is electron donor

Postanoxic denitrification: methanol? مرجع : مرجع المرجع : مرجع المرجع : مرجع : م Aerobic / Anoxic nitrification Return activated sludge Called "endogenous driven" Endogenous decay of cells supplies electron donors -> slower rate of reaction, requires longer retention fimes sometimes supplementary source of carbon (electron donor) added : methanol or acetate  $5CH_2 OH + 6NO_3^- \rightarrow 3N_2 + 5CO_2 + 7H_2O + 6 OH^-$ Methanol Acetate SCH\_COOH + BNO\_ -> 4N2 + 10 CO2 + 6H20 + BOH DO < 0.2 mg/L in bulk liquid Conditions = Actual DO in floc can be less than bulk liquid and nitrification and dentrification may proceed simultaneously: Acrobic zone 02  $N_2 \in$ Anoxic Floc BUK NO3 > CO2 tiquid NH4 Dissolved substrate

the second state the second state the second second

Other options include a "two-sludge" system: Nitrification Methanol -Secondary Clarifier Air Primary darifier Air clarifier do Nitrification Dent. tank Race-track oxidation deteh Pump and aerators Acrobic 4 Influent -Anoxic effluent Same in principle as preanoxic system Rate processes Reachons are represented in same general form : Mg = Mmax 5+Ks coefficient values differ: Hmax Ka Substrate subst. g VSS VSS 5 g VSS-d g subst. m3 Heterotrophs 5-40 0.3-0.5 6COD 3-13 NH4-N Nitrification 0.2 - 0.9 0.5-1.0 0.1-0.15 Dentrification 3.2 9\_ COD 0.4 w/methanol COP (methanol) 0.5 - 2 9-13 0.17 

Lecture 20, Part 2 - Biological Phosphorus Rev	noval	
Phosphorus in wastewater freatment plo	INT EFFICENT	<u>&gt;</u>
is a concern because P is usually	the limiting	)
nutrient in fresh water bodies		
Pin effluent can theretore cause eutre	ophication	
of lakes and rivers		
Typical P concentrations:	Total P	Soluble P
Untreated domestic wastewater -	10 mg/L	7 mg/L
After primary treatment -	8	7
After secondary treatment -	7	7
		4
Typical removal in secondary biologica	al treatment	- :
15 10 to 30 70		
To mater- molity limited strains offly	ionat limite of	ôr P
In water- quanty hourses streams, etc.		
are set at U.1 to 2 mg/L		
· · · · ·		· · · · · ·
Phosphorus chemistry =		
. Phosphorus analytical chemistry is tru	cty because	~ <del>~</del>
there are not analytical methods	to quantify	
the forms of P important for bic	ita	i 
Ironically, P. cycling through organis	ms is well	
understood because there are rad	io active	<u></u>
isotopes of P that can be used	as tracers	,
		· · · · · · · · · · · · · · · · · · ·
Analytically determined P forms:		-   
	<u>, , , , , , , , , , , , , , , , , , , </u>	······································
Total P (TP)	·····	
Particulate D - trapped b	~ 046-110	filter
Soluble P - passes thru' fil	ter	
Soluble reactive P -	measured by	
molybdate blue v	nethod (with	out
acid diaestion)	= ortho-P	;
Soluble unreactive P-	remainder	

	Forms of phosphorus available to microorganisms:
	Soluble reactive P
	= orthophosphate PO4 3-
	Polyphosphates from detergents are also a concern
	e.g. sodium tripolyphosphate NasP3010
Boil in	Acid digestion of sample causes polyphosphates
H2 SO4 for	to break down to orthophosphates - then
90 min.	measure with molybdate blue method to get
	Total inorganic P = ortho-P + polyphosphate
•	In environment, polyphosphates hydrolyze to
	form ortho-P over time
	strong acid digestion (nitric or perchloric acid)
	of unfiltered sample breaks down organic
, 	particulates to ortho -P, - then measure
	with molybdate blue to get Total P =
	Total inorganic P + organic P
	Summary:
	No digestion - ortho-P
	H2SOq acid digestion - Inorganic P = ortho-F
	strong acid digestion - Total P = inorganic
	+ organic
1	Above can be done on filtrate of 0.45-um
	filter to get soluble fraction or on
	unfiltered sample to get totals
······································	:

Sec. Sugar

.

- % <u>></u>%

. تعت

ころみて気をしてもも見てい

. مەرەپىرىيۇلاشىي بىل ئىپرېيۇنىڭ سەخلى - بايۇنىكىسى، . Svinhans

and the same starting after

an marine in

2/

BIO	ogical P removal systems are designed to create
	conditions favorable to Phosphorus Accumulating
	Organisms (PAOs)
	Certain bacteria (e.g. Acinetobacter) synthesize
	polyphosphates and store it in their cellular
-	material - process is sometimes called "luxury uptake
PA	Os are favored by alternating aerobic / anaerobic condition
	First step is anaerobic:
	Available carbon and electrons are stored in
	polyhydroxybutyrate (PHB) and other
-	volatile fally acids. This storage is not
<b>.</b>	done if electron acceptors like 0, or NO2
	are present, hence the need for anaerobic
-	conditions. Simultaneously, polyphosphate
	is broken down and ortho-P is reliased to
	mixed liquor (see Figure 1-23 from M3E, pg 4)
	Next step is peropic or anoxic (denitrifying):
	Bacteria metabolize stored PHB, uptake ortho-P.
	stored as poly-P within cell material. Cells
	become enriched in polyphosphates
	that the is many the R- way alog deally
	Last slop is removal of 1- entricine ceris
	with cells.
	·····
Ke	y to success of P removal is encouraging the
gr	owth of the particular types of bacteria
Ť	at accumulate P.
Th	e anaerobic reactor causes fermentation that breaks
do	wn COD to acetate; a substrate preferred by
P	tOs. This step is sometimes called the "selector"
5	nce it favors (selects for) PAOS.

3/



Adapted from: Rittman, Bruce E., and Perry L. McCarty. *Environmental Biotechnology: Principals and Applications*. New York, NY: McGraw-Hill, 2001.



Adapted from: Rittman, Bruce E., and Perry L. McCarty. *Environmental Biotechnology: Principals and Applications*. New York, NY: McGraw-Hill, 2001.



Fate of soluble BOD and phosphorus in nutrient removal reactor.

Adapted from: G. Tchobanoglous, F. L. Burton, and H. D. Stensel. *Wastewater Engineering: Treatment and Reuse*. 4th ed. Metcalf & Eddy Inc., New York, NY: McGraw-Hill, 2003, p. 626.

5 configurations for biological P removal Predenitrification: (also called A20 process) Nitrate recycle secondary clarifier Anaerobic Aerobic Anoxic > Effluent Influent. (denitrif.) from primary treatment Sludge recycle ➤ sludge wasting Preanoxic nitrogen removal process Bardenpho process : Secondary Nitrate recycle Clarifier ſ Influent Anaerobic Anoxic Aerobic Anoxic Acrobic 1-2 mg/L from phosphorvs primary sludge recycle -8 mg/L P Achieves added N removal Removes 9390 total N, 6590 total P 1

Phostrip, process = Secondary clarifier Influent Aerobic > Effluent ( ~ 1 mg/L P) from primary reactor n 8 mg/L P sludge recycle "Side-stream lime Pstripping High P supernatant Chemical P Anaerobic precipitation reactor 30-70 mig/L P LOW-P anaerobic recycle Recipitate to waste waste Hydrolysis in anaerobic reactor releases poly-P to water (supernatant) - 30-70 mg P/L Addition of lime to precipitator tank raises pH to 11, causes cas (PO4)2 (s) to precipitate Requires more sophisticated operation than alternatives above Most effective P removal is through Chemically Enhanced Primary Treatment (CEPT) - discussed in later lecture

Sequencing batch reactor (SBR) Rather than continuous flow through sequence of tanks for different treatment steps, all steps are done sequentially in a single tank For conventional AST: Influent-Step 1 - Fill (add substrate) î 4 02 Step 2 - React <u>ð</u>, Step 3 - Settle Step 4 - Draw Effluent (decant effluent) the state Step 5 - Idle (waste sludge) > sludok SBRS are very Elexible as to steps, making it possible to add anoxic and anacrobic steps to the sequence for N or P removal

7/

SBR For P removal Step 1 - Fill Step 2 - Anaerobic react (tank is mixed but without aeration) Step 3 - Aerobic react Step 4 - Anoxic react (denitrification) (Note: steps 3 and 4 may be repeated) Step 5 - Settle Step 6 - Decant Step 7 - Idle (waste sludge) ş ÷

8/

and a second second



Adapted from: G. Tchobanoglous, F. L. Burton, and H. D. Stensel. Wastewater Engineering: Treatment and Reuse. 4th ed. Metcalf & Eddy Inc., New York, NY: McGraw-Hill, 2003, p. 813.