

Introduction to Python

LinuxWorld - New York City - January 2002

Guido van Rossum
Director of PythonLabs at Zope Corporation





Why Python?

- Have your cake and eat it, too:
Productivity **and** readable code
- VHLLs will gain on system languages
(John Ousterhout)
- "Life's better without braces"
(Bruce Eckel)

ZOPE



Tutorial Outline

- interactive "shell"
- basic types: numbers, strings
- container types: lists, dictionaries, tuples
- variables
- control structures
- functions & procedures
- classes & instances
- modules & packages
- exceptions
- files & standard library
- what's new in Python 2.0 and beyond

ZOPE



Try It Out!

- If you brought a laptop into the classroom, feel free to play along
- Download Python from www.python.org
- Any version will do for this class
 - By and large they are all mutually compatible
 - Recommended version: 2.1.1 or 2.2
 - Oldest version still in widespread use: 1.5.2
 - Avoid 1.6/1.6.1 if you can
 - When using 2.0 or 2.1, upgrade to 2.0.1 / 2.1.1
 - 2.1.2 is coming soon!
- Use IDLE if you can

ZOPE



Interactive “Shell”

- Great for learning the language
- Great for experimenting with the library
- Great for testing your own modules
- Two variations: IDLE (GUI),
python (command line)
- Type statements or expressions at prompt:

```
>>> print "Hello, world"
```

```
Hello, world
```

```
>>> x = 12**2
```

```
>>> x/2
```

```
72
```

```
>>> # this is a comment
```

ZOPE

- The usual suspects
 - 12, 3.14, 0xFF, 0377, (-1+2)*3/4**5, abs(x), 0<x<=5
- C-style shifting & masking
 - 1<<16, x&0xff, x|1, ~x, x^y
- Integer division truncates :-(
 - 1/2 -> 0 # 1./2. -> 0.5, float(1)/2 -> 0.5
 - Will be fixed in the future
- Long (arbitrary precision), complex
 - 2L**100 -> 1267650600228229401496703205376L
 - In Python 2.2 and beyond, 2**100 does the same thing
 - 1j**2 -> (-1+0j)



Strings

- "hello"+ "world" "elloworld" # concatenation
- "hello" * 3 "hellohellohello" # repetition
- "hello"[0] "h" # indexing
- "hello"[-1] "o" # (from end)
- "hello"[1:4] "ell" # slicing
- len("hello") 5 # size
- "hello" < "jello" 1 # comparison
- "e" in "hello" 1 # search
- "escapes: \n etc, \033 etc, \if etc"
- 'single quotes' """"triple quotes"""" r"raw strings"

ZOPE

- Flexible arrays, *not* Lisp-like linked lists
 - `a = [99, "bottles of beer", ["on", "the", "wall"]]`
- Same operators as for strings
 - `a+b, a*3, a[0], a[-1], a[1:], len(a)`
- Item and slice assignment
 - `a[0] = 98`
 - `a[1:2] = ["bottles", "of", "beer"]`
 $\rightarrow [98, "bottles", "of", "beer", ["on", "the", "wall"]]$
 - `del a[-1]` # $\rightarrow [98, "bottles", "of", "beer"]$



More List Operations

```
>>> a = range(5)                      # [0,1,2,3,4]
>>> a.append(5)                        # [0,1,2,3,4,5]
>>> a.pop()                            # [0,1,2,3,4]
5
>>> a.insert(0, 42)                    # [42,0,1,2,3,4]
>>> a.pop(0)                            # [0,1,2,3,4]
5.5
>>> a.reverse()                        # [4,3,2,1,0]
>>> a.sort()                            # [0,1,2,3,4]
```

ZOPE

- Hash tables, "associative arrays"
 - `d = {"duck": "eend", "water": "water"}`
- Lookup:
 - `d["duck"] -> "eend"`
 - `d["back"] # raises KeyError exception`
- Delete, insert, overwrite:
 - `del d["water"] # {"duck": "eend", "back": "rug"}`
 - `d["back"] = "rug" # {"duck": "eend", "back": "rug"}`
 - `d["duck"] = "duik" # {"duck": "duik", "back": "rug"}`



More Dictionary Ops

- Keys, values, items:
 - `d.keys() -> ["duck", "back"]`
 - `d.values() -> ["duik", "rug"]`
 - `d.items() -> [("duck","duik"), ("back","rug")]`
- Presence check:
 - `d.has_key("duck") -> 1; d.has_key("spam") -> 0`
- Values of any type; keys almost any
 - `{"name":"Guido", "age":43, ("hello","world"):1, 42:"yes", "flag": ["red","white","blue"]}`

ZOPE



Dictionary Details

- Keys must be **immutable**:
 - numbers, strings, tuples of immutables
 - these cannot be changed after creation
 - reason is *hashing* (fast lookup technique)
 - **not** lists or other dictionaries
 - these types of objects can be changed "in place"
 - no restrictions on values
- Keys will be listed in **arbitrary order**
 - again, because of hashing

ZOPE

- `key = (lastname, firstname)`
- `point = x, y, z # parentheses optional`
- `x, y, z = point # unpack`
- `lastname = key[0]`
- `singleton = (1,) # trailing comma!!!`
- `empty = () # parentheses!`
- tuples vs. lists; tuples immutable

- No need to declare
- Need to assign (initialize)
 - use of uninitialized variable raises exception
- Not typed
 - if friendly: greeting = "hello world"
 - else: greeting = 12**2
 - print greeting
- ***Everything*** is a "variable":
 - Even functions, classes, modules



Reference Semantics

- Assignment manipulates references
 - $x = y$ **does not make a copy** of y
 - $x = y$ makes x **reference** the object y references
- Very useful; but beware!
- Example:


```
>>> a = [1, 2, 3]
>>> b = a
>>> a.append(4)
>>> print b
[1, 2, 3, 4]
```

ZOPE




Changing a Shared List


a = [1, 2, 3]



b = a




a.append(4)




ZOPE

Changing an Integer


a = 1



b = a



a = a+1



new int object created
by add operator (1+1)

old reference deleted
by assignment (a=...)

ZOPE



Control Structures

if condition:

statements

[elif condition:

statements] ...

else:

statements

while condition:

statements

for var in sequence:

statements

break

continue

ZOPE



Grouping Indentation

In Python:

```
for i in range(20):
    if i%3 == 0:
        print i
    if i%5 == 0:
        print "Bingo!"
    print "---"
```

In C:

```
for (i = 0; i < 20; i++)
{
    if (i%3 == 0) {
        printf("%d\n", i);
        if (i%5 == 0) {
            printf("Bingo!\n");
        }
        printf("---\n");
    }
}
```

```
0
Bingo!
---
---
---
3
---
---
6
---
9
---
12
---
---
15
Bingo!
---
---
18
---
```

ZOPE



Functions, Procedures

```
def name(arg1, arg2, ...):  
    """documentation"""\n    # optional doc string  
  
    statements  
  
  
  
  
    return\n    # from procedure  
  
    return expression\n    # from function
```

ZOPE



Example Function

```
def gcd(a, b):  
    "greatest common divisor"  
    while a != 0:  
        a, b = b%a, a    # parallel assignment  
    return b
```

```
>>> gcd.__doc__  
'greatest common divisor'  
>>> gcd(12, 20)
```

4

ZOPE

class name:

"documentation"

statements

-or-

class name(base1, base2, ...):

...

Most, *statements* are method definitions:

def name(self, arg1, arg2, ...):

...

May also be *class variable* assignments



Example Class

class Stack:

"A well-known data structure..."

```
def __init__(self):          # constructor
```

```
    self.items = []
```

```
def push(self, x):
```

```
    self.items.append(x)      # the sky is the limit
```

```
def pop(self):
```

```
    x = self.items[-1]        # what happens if it's
empty?
```

```
    del self.items[-1]
```

```
    return x
```

```
def empty(self):
```

```
    return len(self.items) == 0    # Boolean result
```

ZOPE



Using Classes

- To create an instance, simply call the class object:

```
x = Stack()      # no 'new' operator!
```

- To use methods of the instance, call using dot notation:

```
x.empty()      # -> 1
```

```
x.push(1)          # [1]
```

```
x.empty()      # -> 0
```

```
x.push("hello")    # [1, "hello"]
```

```
x.pop()          # -> "hello"    # [1]
```

- To inspect instance variables, use dot notation:

```
x.items      # -> [1]
```

ZOPE



Subclassing

```
class FancyStack(Stack):
    "stack with added ability to inspect inferior stack items"

    def peek(self, n):
        "peek(0) returns top; peek(-1) returns item below that; etc."
        size = len(self.items)
        assert 0 <= n < size                      # test precondition
        return self.items[size-1-n]
```

ZOPE



Subclassing (2)

```
class LimitedStack(FancyStack):
    "fancy stack with limit on stack size"

    def __init__(self, limit):
        self.limit = limit
        FancyStack.__init__(self)          # base class
constructor

    def push(self, x):
        assert len(self.items) < self.limit
        FancyStack.push(self, x)          # "super" method call
```

ZOPE



Class / Instance Variables

```
class Connection:  
    verbose = 0                      # class variable  
    def __init__(self, host):  
        self.host = host                # instance variable  
    def debug(self, v):  
        self.verbose = v                # make instance variable!  
    def connect(self):  
        if self.verbose:                # class or instance variable?  
            print "connecting to", self.host
```

ZOPE



Instance Variable Rules

- On use via instance (`self.x`), search order:
 - (1) instance, (2) class, (3) base classes
 - this also works for method lookup
- On assignment via instance (`self.x = ...`):
 - always makes an instance variable
- Class variables "default" for instance variables
- But...!
 - mutable *class* variable: one copy *shared* by all
 - mutable *instance* variable: each instance its own

ZOPE

- Collection of stuff in *foo.py* file
 - functions, classes, variables
- Importing modules:
 - import re; print re.match("[a-z]+", s)
 - from re import match; print match("[a-z]+", s)
- Import with rename:
 - import re as regex
 - from re import match as m
 - Before Python 2.0:
 - import re; regex = re; del re



Packages

- Collection of modules in directory
- Must have `__init__.py` file
- May contain subpackages
- Import syntax:
 - `from P.Q.M import foo; print foo()`
 - `from P.Q import M; print M.foo()`
 - `import P.Q.M; print P.Q.M.foo()`
 - `import P.Q.M as M; print M.foo() # new`

ZOPE



Catching Exceptions

```
def foo(x):  
    return 1/x
```

```
def bar(x):  
    try:  
        print foo(x)  
    except ZeroDivisionError, message:  
        print "Can't divide by zero:", message
```

```
bar(0)
```

ZOPE



Try-finally: Cleanup

```
f = open(file)
try:
    process_file(f)
finally:
    f.close()      # always executed
print "OK" # executed on success only
```

ZOPE



Raising Exceptions

- raise IndexError
- raise IndexError("k out of range")
- raise IndexError, "k out of range"
- try:

something

```
except: # catch everything
        print "Oops"
        raise # reraise
```

ZOPE



More on Exceptions

- User-defined exceptions
 - subclass Exception or any other standard exception
- Old Python: exceptions can be strings
 - WATCH OUT: compared by object identity, not ==
- Last caught exception info:
 - `sys.exc_info() == (exc_type, exc_value, exc_traceback)`
- Last uncaught exception (traceback printed):
 - `sys.last_type, sys.last_value, sys.last_traceback`
- Printing exceptions: traceback module

ZOPE



File Objects

- `f = open(filename[, mode[, bufsize]])`
 - mode can be "r", "w", "a" (like C stdio); default "r"
 - append "b" for text translation mode
 - append "+" for read/write open
 - bufsize: 0=unbuffered; 1=line-buffered; buffered
- methods:
 - `read([nbytes])`, `readline()`, `readlines()`
 - `write(string)`, `writelines(list)`
 - `seek(pos[, how])`, `tell()`
 - `flush()`, `close()`
 - `fileno()`

ZOPE

- Core:
 - os, sys, string, getopt, StringIO, struct, pickle,
...
...
- Regular expressions:
 - re module; Perl-5 style patterns and matching rules
- Internet:
 - socket, rfc822, httplib, htmlllib, ftplib, smtplib, ...
- Miscellaneous:
 - pdb (debugger), profile+psutil
 - Tkinter (Tcl/Tk interface), audio, *dbm, ...



Python 2.0: What's New

- Augmented assignment: `x += y`
- List comprehensions:
`[s.strip() for s in f.readlines()]`
- Extended print: `print >>sys.stderr, "Hello!"`
- Extended import: `import foo as bar`
- Unicode strings: `u"\u1234"`
- New re implementation (faster, Unicode)
- Collection of cyclic garbage
- XML, distutils

ZOPE



Python 2.1: What's New

- From `__future__` import nested_scopes
 - def make_adder(*n*):
 def adder(*x*): return *x+n*
 return adder
 - add2 = make_adder(2)
 - add2(10) == 12
- Rich comparisons
 - Overload `<`, `<=`, `==`, `!=`, `>=`, `>` separately
- Warnings framework
 - Prepare for the future

ZOPE



Python 2.2: What's New

- Iterators and Generators
 - from __future__ import generators
 - def inorder(tree):
 - if tree:
 - for x in inorder(tree.left): *yield* x
 - yield* tree.label
 - for x in inorder(tree.right): *yield* x
- Type/class unification
 - class mydict(dict): ...
- Fix division operator so $1/2 == 0.5$; $1//2 == 0$
 - Requires __future__ statement in Python 2.x
 - Change will be permanent in Python 3.0

ZOPE

- <http://www.python.org>
 - official site
- <http://starship.python.net>
 - Community
- <http://www.python.org/psa/bookstore/>
 - (alias for <http://www.amk.ca/bookstore/>)
 - Python Bookstore



Further Reading

- Learning Python: Lutz, Ascher (O'Reilly '98)
- Python Essential Reference: Beazley (New Riders '99)
- Programming Python, 2nd Ed.: Lutz (O'Reilly '01)
- Core Python Programming: Chun (Prentice-Hall '00)
- The Quick Python Book: Harms, McDonald (Manning '99)
- The Standard Python Library: Lundh (O'Reilly '01)
- Python and Tkinter Programming: Grayson (Manning '00)
- Python Programming on Win32:
Hammond, Robinson (O'Reilly '00)
- Learn to Program Using Python: Gauld (Addison-W. '00)
- And many more titles...

ZOPE

TIME FOR QUESTIONS

