




Lecture 6: Methods

MIT-AITI Kenya 2005


In this lecture, you will learn...

- What a method is
- Why we use methods
- How to declare a method
- The four parts of a method
- How to invoke a method
- The purpose of the main method
- And see some example methods




The Concept of a Method

- Methods also known as functions or procedures.
- Methods are a way of capturing a sequence of computational steps into a reusable unit.
- Can you think of places where you might want to use methods?



The Concept of a Method

- Methods also known as functions or procedures.
- Methods are a way of capturing a sequence of computational steps into a reusable unit.
- Can you think of places where you might want to use methods?
 - evaluate the quadratic formula, print to the screen





The Concept of a Method (con't)

- Methods can accept inputs in the form of *arguments*
- They can then perform some operations with the arguments
- And can *return* a value that is the result of the computations, which is also known as the output




Square Root Method

- Square root is a good example of a method.
 - The square root method accepts a single number as an argument and returns the square root of that number.




Square Root Method (con't)

- The computation of square roots involves many intermediate steps between input and output.
- When we use square root, we don't care about these steps. All we need is to get the correct output.
- Hiding the internal workings of a method from a user but providing the correct answer is known as *abstraction*




Methods Pop Quiz

- What is the name given to the inputs of a method?




Methods Pop Quiz

- What is the name given to the inputs of a method?
 - Arguments




Methods Pop Quiz

- What is the name given to the inputs of a method?
 - Arguments
- Why do we use methods?




Methods Pop Quiz

- What is the name given to the inputs of a method?
 - Arguments
- Why do we use methods?
 - To capture a sequence of steps which can
 - later be reused




Methods Pop Quiz

- What is the name given to the inputs of a method?
 - Arguments
- Why do we use methods?
 - To capture a sequence of steps which can
 - later be reused
- What is the name given to hiding the internal workings of a method?



Methods Pop Quiz

- What is the name given to the inputs of a method?
 - Arguments
- Why do we use methods?
 - To capture a sequence of steps which can
 - later be reused
- What is the name given to hiding the internal workings of a method?
 - Abstraction



Declaring Methods

- A method has 4 parts: the return type, the name, the arguments, and the body:

type name arguments


double **sqrt**(double num) {
body { // a set of operations that compute
 // the square root of a number
 }

- The type, name and arguments together is referred to as the ***signature*** of the method



The Return Type of a Method


- The return type of a method may be any data type.
- The type of a method designates the data type of the output it produces.
- Methods can also return nothing in which case they are declared void.



Return Statements


- The return statement is used in a method to output the result of the methods computation.
- It has the form:
 - `return expression_value;`
- The type of the `expression_value` must be the same as the type of the method:

```
double sqrt(double num) {  
    double answer;  
    // Compute the square root of num  
    // and store in answer  
    return answer;  
}
```



Return Statements (con't)


- A method exits immediately after it executes the return statement
- Therefore, the return statement is usually the last statement in a method
- A method may have multiple return statements. Can you think of an example of such a case?



Multiple Returns


- An example using multiple returns:

```
int absoluteValue (int num){  
    if (num < 0)  
        return -num;  
    else  
        return num;  
}
```




void Methods

- A method of type **void** has a return statement without any specified value. i.e. **return;**
- This may seem useless, but in practice void is used often.
- A good example is when a methods only purpose is to print to the screen.
- If no return statement is used in a method of type void, it automatically returns at the end



Method Arguments


- Methods can take input in the form of arguments.
- Arguments are used as variables inside the method body.
- Like variables, arguments must have their type specified.
- Arguments are specified inside the parentheses that follow the name of the method.



Example Method

- Here is an example of a method that divides two doubles:

```
double divide(double a, double b) {  
    double answer;  
    answer = a / b;  
    return answer;
```




Method Arguments

- Multiple method arguments are separated by commas:

```
double pow(double x, double y)
```


- Arguments may be of different types

```
int indexOf(String str, int fromIndex)
```



The Method Body

- The body of a method is a block specified by curly brackets i.e { }. The body defines the actions of the method.
- The method arguments can be used anywhere inside of the body.
- All methods must have curly brackets to specify the body even if the body contains only one statement or no statements.




Invoking Methods

- To call a method, specify the name of the method followed by a list of comma separated arguments in parentheses:

```
pow( 2 , 10 ) ; //Computes  $2^{10}$ 
```

- If the method has no arguments, you still need to follow the method name with empty parentheses:

```
size( );
```




Static Methods

- Some methods have the keyword **static** before the return type:

```
static double divide(double a, double b) {  
    return a / b;  
}
```


- We'll learn what it means for a method to be static in a later lecture
- For now, all the methods we write in lab will be static.



main – A Special Method

- The only method that we have used in lab up until this point is the **main** method.
- The main method is where a Java program always starts when you run a class file
- The **main** method is static and has a strict signature which must be followed:

```
public static void main(String[] args) {  
    . . .  
}
```




main Method (con't)

```
class SayHi {  
    public static void main(String[] args) {  
        System.out.println("Hi, " + args[0]);  
    }  
}
```

- If you were to type `java Program arg1 arg2 ... argN` on the command line, anything after the name of the class file is automatically entered into the `args` array:


```
java SayHi Sonia
```

- In this example `args[0]` will contain the String "Sonia", and the output of the program will be "Hi, Sonia".



Methods Pop Quiz 2

- What are the four parts of a method and what are their functions?



Methods Pop Quiz 2


- What are the four parts of a method and what are their functions?

Return type – data type returned by the method

Name – name of the method


Arguments – inputs to the method

Body – sequence of instructions executed by the method



Methods Pop Quiz 2 (con't)


- What is used to separate multiple arguments to a method?



Methods Pop Quiz 2 (con't)


- What is used to separate multiple arguments to a method?

Comma



Methods Pop Quiz 2 (con't)

- What is used to separate multiple arguments to a method?
Comma
- What is used to outline the body of a method?




Methods Pop Quiz 2 (con't)

- What is used to separate multiple arguments to a method?

Comma


- What is used to outline the body of a method?

Curly brackets { }




Methods Pop Quiz 2 (con't)

- What is used to separate multiple arguments to a method?
Comma
- What is used to outline the body of a method?
Curly brackets { }
- How do you invoke a method?




Methods Pop Quiz 2 (con't)

- What is used to separate multiple arguments to a method?
Comma
- What is used to outline the body of a method?
Curly brackets { }
- How do you invoke a method?
Specify the name of the method followed by a list of comma-separated arguments in parentheses,
i.e. method_name(arg1, arg2, ..., argn)



What is wrong with the following ?


```
static double addSometimes(num1, num2) {  
    double sum;  
    if (num1 < num2) {  
        sum = num1 + num2;  
        String completed = "completed";  
        return completed;  
    }  
}
```



What is wrong with the following ?

```
static double addSometimes(num1, num2) {  
    double sum;  
    if (num1 < num2) {  
        sum = num1 + num2;  
        String completed = "completed";  
        return completed;  
    }  
}
```

- Types for the arguments num1 and num2 are not specified
- String completed does not match the correct double return type
- Method addSometimes does not always return an answer. This will cause an error in Java because we specified that addSometimes would always return a double.




Example main method

```
class Greetings {  
    public static void main(String args[]) {  
        String greeting = "";  
        for (int i=0; i < args.length; i++) {  
            greeting += "Jambo " + args[i] + " ! " ;  
        }  
        System.out.println(greeting);  
    }  
}
```

- After compiling, if you type


```
java Greetings Alice Bob Charlie  
prints out "Jambo Alice! Jambo Bob! Jambo Charlie!"
```



Another Example


```
class Max {  
    public static void main(String args[]) {  
        if (args.length == 0) return;  
  
        int max = Integer.parseInt(args[0]);  
        for (int i=1; i < args.length; i++) {  
            if (Integer.parseInt(args[i]) > max) {  
                max = Integer.parseInt(args[i]);  
            }  
        }  
        System.out.println(max);  
    }  
}
```

- After compiling, if you type `java Max 3 2 9 2 4` the program will print out 9



Important Points Covered

- Methods capture a piece of computation we wish to perform repeatedly into a single abstraction
- Methods in Java have 4 parts: return type, name, arguments, body.
- The return type and arguments may be either primitive data types (i.e. int) or complex data types (i.e. Objects), which we will cover next lecture
- **main** is a special Java method which the java interpreter looks for when you try to run a class file
- **main** has a strict signature that must be followed:
`public static void main(String args[])`



MIT OpenCourseWare
<http://ocw.mit.edu>

EC.S01 Internet Technology in Local and Global Communities
Spring 2005-Summer 2005

For information about citing these materials or our Terms of Use, visit: <http://ocw.mit.edu/terms>.