


6.978/ESD.68

Competition in Access Networks


Sharon E. Gillett, MIT

The past: Silos



From (Clark, 1999)

The present: "Convergence"



From (Clark, 1999)

The Future(?): Internet as Platform





Figure 4: Potential industry structure surrounding the Internet.


From (Clark, 1999)

Wireless Telephony Competing With Fixed Lines, 2002



(1) 1990-1998 data from "FCC Trends in Telephone Service May 2002"; 1999-2002 data from "FCC, Local Telephone Competition: Status as of Dec 31 2002"; (2) CTIA Semi-Annual Wireless Industry Survey, published 2003; (3) 99-2001:FCC.COM: Trends in Telephone Service May 2002 (High Speed Lines with 200Kbps in at least one direction; Legg Mason Wood Walker, Inc. "Coming Down the Pipe - Interim Report 4Q 2002/1Q 2003 Industry Update - March 13, 2003"; (4) NCTA, "Residential Cable Telephony Subscribers"

OECD Broadband subscribers per 100 inhabitants, by technology, June 2006




Source: OECD

Courtesy of OECD. Source: OECD Broadband Statistics, <http://www.oecd.org/sti/ict/broadband>. © OECD, 2006.

3. Broadband Technologies

Network Architecture

- Generic model of a broadband access network
 - *system architecture common across technology alternatives*
 - *important differences in cost-performance and business models*




Wireline Options

- Hybrid fiber-coax
 - DOCSIS
 - Role of fiber (toward FTTC)
- Digital subscriber line (DSL)
 - Distance, crosstalk
 - Role of fiber (toward FTTC)
- Optical fiber
 - Flavors of fiber to the home (FTTH)
 - Depends on what “kind of “ FTTH: not all the same
 - Service based on equipment at both ends
 - High-performance endpoint—highest cost
- Powerline


DSL/Fiber Architecture

- **Same architecture evolves naturally from ADSL to VDSL to FTTC/FTTH**
 - *switching equipment tends to migrate closer to subscribers (..remote DSLAM, gigabit Ethernet switches, etc.)*
 - *system deployment cost dominated by physical wiring, due to rapid improvements in switching & transport cost/performance*




HFC Architecture

- **Broadband access over cable based on shared access (DOCSIS standard) to existing TV coax**
 - *Medium access control (MAC) protocol for coax sharing*
 - *Signal converted to analog fiber at remote node*
 - *System cost dominated by fiber upgrade investments, due to rapidly falling cost of DOCSIS modems & switching gear*
 - *Also evolves naturally towards FTTC/FTTH*



One Architecture for BPL




Wireless Options

- **Mobile/3G**
 - Future: seamless mobile & portable broadband
 - Reality: emerging 3G falling short of hype (capacity, speed..)
- **WLAN**
 - 802.11, unlicensed 2.4 and 5 Ghz bands
 - Bottom-up deployment is accelerating... (airports, offices, homes..)
- **FWA (Fixed Wireless Access)**
 - MMDS, LMDS,...
 - much potential, but uncertain business conditions ...
- **Satellite**
 - Geo-synchronous (GEOS) & Low-earth orbit (LEOS)
 - Viable for certain markets, but with capacity limitations...

Wireless Architecture


- **Broadband wireless based on shared access of radio medium (MMDS, LMDS, 3G, WLAN,..)**
 - *MAC protocol for shared use of radio (..similar to cable modems)*
 - *Switching or routing beyond access point (...similar to DSL)*
 - *FWA, satellite, WLAN & 3G/mobile as potential options, each with different entry cost and system cost/performance trade-offs*




Local Access Techs in Context

- Total cost and performance depends on more than just local access
- Local access aggregates traffic from multiple premises at POPs, funnels to higher-capacity links
- “Second mile” connects to upstream aggregation
- Broadband providers pay for Internet transit service or establish peering arrangements
- Caches, service-supporting servers at POPs


Unbundling DSL



Sub-loop Unbundling



ADSL Spectrum Allocation (Line Sharing)



Open Access and Layering

Layer:	Municipality provides...
0	Conduit and collocation facilities.
1 (Physical Layer Unbundling)	Dark fiber leasing, or perhaps, Optical Layer unbundling (CWDM or DWDM in PONs)
2 (Data Link Layer Unbundling)	Dark fiber and link-layer electronics at each end. For example, Ethernet-based VLAN, or ATM-based PVCs.
3 (Network Layer Unbundling)	Basic network service provided. For example, IP Layer 3 service over cable using policy-based routing to multiple ISPs

Regulatory Dilemma


Heisenberg's Uncertainty Principle:

Can't observe situation without perturbing it

Fundamental Economics	Regulatory Assumption About Competition	Outcome
Competition is sustainable (competitive equilibrium exists)	Sustainable	Free market
	Not sustainable	Regulation stifles innovation, competition
Competition is not sustainable (no competitive equilibrium)	Sustainable	Government-sanctioned, unregulated monopoly
	Not sustainable	Necessarily regulated monopoly

Additional Tech Slides


Internet Access via Cable




Telephone Network Hierarchy

Twisted-pair copper loops dedicated to individual subscribers

- Physical aggregation at “Central Office” (CO) via Main Distribution Frame
- CO Switching: Access
- IXC Switching: Tandem
- Increasing aggregation at each level




Multiplexing and Concentration in CO Switch



Telephone Access Network

Splices represented by 

- Feeder
- Distribution
- Drop
- Aggregation is *physical*:
bundles of wire-pairs



Internet over ADSL (with VoIP)




Figure by MIT OCW.

Telco migration to Fiber-to-the-Neighborhood

