

Topics: Gauss's Law

Related Reading:

Course Notes (Liao et al.): Chapter 4

Topic Introduction

In this class we will practice calculating electric fields using Gauss's law by doing problem solving #3. Remember that the idea behind Gauss's law is that, pictorially, electric fields flow out of and into charges. If you surround some region of space with a closed surface (think bag), then observing how much field “flows” into or out of that surface tells you how much charge is enclosed by the bag. For example, if you surround a positive charge with a surface then you will see a net flow outwards, whereas if you surround a negative charge with a surface you will see a net flow inwards.

Gauss's Law

Gauss's law states that the electric flux through any closed surface is proportional to the total charge enclosed by the surface:

$$\Phi_E = \oiint_S \vec{E} \cdot d\vec{A} = \frac{q_{\text{enc}}}{\epsilon_0}$$

A *closed* surface is a surface which completely encloses a volume, and the integral over a closed surface S is denoted by \oiint .

Symmetry and Gaussian Surfaces

Although Gauss's law is always true, as a tool for calculation of the electric field, it is only useful for highly symmetric systems. The reason for this is that in order to solve for the electric field \vec{E} we need to be able to “get it out of the integral.” That is, we need to work with systems where the flux integral can be converted into a simple multiplication. Examples of systems that possess such symmetry and the corresponding closed *Gaussian surfaces* we will use to surround them are summarized below:

Symmetry	System	Gaussian Surface
Cylindrical	Infinite line	Coaxial Cylinder
Planar	Infinite plane	Gaussian “Pillbox”
Spherical	Sphere, Spherical shell	Concentric Sphere

Solving Problems using Gauss's law

Gauss's law provides a powerful tool for calculating the electric field of charge distributions that have one of the three symmetries listed above. The following steps are useful when applying Gauss's law:

- (1) Identify the symmetry associated with the charge distribution, and the associated shape of "Gaussian surfaces" to be used.
- (2) Divide space into different regions associated with the charge distribution, and determine the exact Gaussian surface to be used for each region. The electric field must be constant or known (i.e. zero) across the Gaussian surface.
- (3) For each region, calculate q_{enc} , the charge enclosed by the Gaussian surface.
- (4) For each region, calculate the electric flux Φ_E through the Gaussian surface.
- (5) Equate Φ_E with $q_{\text{enc}} / \epsilon_0$, and solve for the electric field in each region.

Important Equations

Electric flux through a surface S :

$$\Phi_E = \iint_S \vec{\mathbf{E}} \cdot d\vec{\mathbf{A}}$$

Gauss's law:

$$\Phi_E = \oiint_S \vec{\mathbf{E}} \cdot d\vec{\mathbf{A}} = \frac{q_{\text{enc}}}{\epsilon_0}$$